

Lite-Ex® PL 30

SURPASSES ALL LED FLASHLIGHTS ON THE MARKET.

The Lite-Ex® PL 30 flashlight from ecom surpasses all other LED flashlights on the market.

The integrated 3 Watt LED, which is powered by 3 LR14 batteries, allows work to be conducted with extremely bright light for hours at a time.

The ergonomically designed, anti-static plastic housing ensures the flashlight fits perfectly in your hand and also provides excellent anti-slip protection.

The high IP65 protection rating prevents the permeation of dust and jet water. Use in harsh conditions is therefore not a problem.

SIMPLE AND RELIABLE TWIST MECHANISM

The switch-on mechanism is yet another outstanding feature - the flashlight is switched on via a sturdy rotating ring. This eliminates annoying malfunctions and repairs due to a faulty switch, thereby saving the user both time and money.

Lite-Ex® PL 30 LED FLASHLIGHT FOR ZONE 0 / 20

FEATURES

- Zone 0 / 20
- 1x high performance LED (3 Watt)
- 6,000 lux (1m)
- Ring switch
- Rugged housing
- High IP protection class IP65
- Diaphragm valve for pressure compensation

SCOPE OF DELIVERY

- Lite-Ex® PL 30
- Batteries
- Wrist strap
- User manual
- Ex-certificate
- EC Declaration of Conformity











product
design
award

2007



30 POWER MEETS AWARD

ACCESSORIES

| | ARTICLE NO. | PRODUCT DESCRIPTION |
|---|---|---------------------|
|  | A0002055  | Leather holster |
|  | ET002055  | Sealing kit |
|  | ET002056  | Replacement lens |
|  | ET002059  | Ring switch |



TECHNICAL DATA

| | |
|----------------------------|--|
| Ambient temperature | -20 °C ... +50 °C |
| Storage temperature | -30 °C + 60 °C (without batteries) |
| Power supply | 3x LR 14 (type-tested) |
| Bulb | 1x 3 Watt LED |
| Luminosity | 6,000 lux (at a distance of 1 m) |
| Luminous flux | 135 lumens |
| Operating time | > 48 hrs (continuous operation) |
| Dimensions | approx. 220 x 55 / 42 mm (L x Ø) |
| Weight | approx. 530 g |
| IP protection class | IP65 |
| ESD protection | Anti-static housing |
| CE-designation | CE 0102 |

EX DATA

ATEX



Ⓜ II 1 G Ex ia op is IIC T4
Ⓜ II 1 D iaD 20 T 130°C

IECEX



Ex ia op is IIC T4 Ga
Ex ia IIIC T130°C Da IP65

EMEA

Germany (Headquarters) ¹

ecom instruments GmbH
Industriestraße 2
97959 Assamstadt
Phone +49 62 94 42 24-0
Fax +49 62 94 42 24-100
sales@ecom-ex.com
¹ also covering Austria

ecom Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com
² also covering Belgium and
Luxembourg

France ³

ecom Nied sarl
4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com
³ also covering Algeria, Egypt,
Morocco, Tunisia and Libya

Italy

ecom instruments srl
Via Gandhi, 15 Galleria
20017 Rho (MI)
Phone +39 02 93 90 92 16
Fax +39 02 93 90 62 97
info.it@ecom-ex.com

Switzerland

ecom instruments GmbH
Mercurstraße 2
6210 Sursee
Phone +41 4 19 21 60 00
Fax +41 4 19 22 00 08
info.ch@ecom-ex.com

United Kingdom

ecom instruments ltd
A310, The Wilton Centre,
Redcar, TS10 4RF,
United Kingdom
Phone +44 1642 46 54 00
Fax +44 1642 46 54 02
info.uk@ecom-ex.com

Nordics

ecom instruments GmbH
Postbox 304
2970 Hørsholm
Denmark
Phone +45 28 252 575
info.nordics@ecom-ex.com

Middle East

ecom instruments fze
P.O. Box 8918
Saif-Zone, Sharjah, UAE
Phone +971 6 5 57 34 30
Fax +971 6 5 57 34 31
info.uae@ecom-ex.com

Americas

USA Headquarters

ecom instruments Inc.
1779 Westborough Drive, Suite 102
Katy, Texas 77449
Phone +1 281 496 59 30
Fax +1 281 496 23 21
info.us@ecom-ex.com

Asia

South East Asia

ecom instruments (SEA) Pte Ltd.
12 Arumugam Road
#05-11 Lion Building B
Singapore 409958
Phone +65 61 00 33 29
Fax +65 63 99 33 29
info.sg@ecom-ex.com

