

Apparathjul Institutional castors

























Ø 50-75 mm

 40-80 kg



Apparathjul med sort, afsmitningsfri gummibane og kunststofcenter, eller helstøbte kunststoffjul.
Galvaniserede og sortmalede, rivetterede gafler med dobbelt kuglekrans i drejeled og bremsegafler med lås på både hjul og drejefunktion.
Anvendelsestemperatur: -20°C til +70°C.

Institutional wheels with black, non-marking rubber tread and plastic centre, or thermoplastic wheels.
Galvanized and painted, riveted brackets with double ball race in the swivel head, brake locks both wheel and swiveling motion.
Temperature range: -4°F to +158°F.

		VARENUMMER ARTICLE NO.						MONTERINGSMÅL MOUNTING MEASUREMENTS						HJULDIMENSIONER WHEEL DIMENSIONS			
																	
Gummibane / Rubber tread																	
50		40	5763125	5763325	5763425	5763555	5763725	73	25	60x60	47x47	6	10	75	18	23	6
75		50	5763135	5763335	5763435	5763565	5763735	100	25	60x60	47x47	6	10	85	24	28	6
Kunststof / Nylon wheels																	
50		40	5264125	5264325	5264425	5264555	5264725	73	25	60x60	47x47	6	10	75	18	23	6
75		50	5264135	5264335	5264435	5264565	5264735	100	25	60x60	47x47	6	10	85	24	28	6
Dobbelthjul med gummibane / Twin wheels with rubber tread																	
50		60	5776125	5776325	5776425	5776555	5776725	73	25	60x60	47x47	6	10	88	2x18	48	6
75		80	5776135	5776335	5776435	5776565	5776735	100	35	60x60	47x47	6	10	108	2x24	58	6
Dobbelthjul med kunststof / Twin wheels in nylon																	
50		60	5274125	5274325	5274425	5274555	5274725	73	25	60x60	47x47	6	10	88	2x18	48	6
75		80	5274135	5274335	5274435	5274565	5274735	100	35	60x60	47x47	6	10	108	2x24	58	6

Alle mål er i mm
All measurements are in mm

Fås også i hvid.
Also available in white castors.

