







28II EX

ROBUST AND INTRINSICALLY SAFE

CERTIFICATION	
ATEX 	<ul style="list-style-type: none"> II 2 G Ex ia IIC T4 Gb I M1 Ex ia I Ma
IECEX 	<ul style="list-style-type: none"> Ex ia IIC T4 Gb Ex ia I Ma
NEC/CEC 	<ul style="list-style-type: none"> Class I, Division 1, Groups A,B,C,D Class I Zone 1 AEx ia IIC T4 Ex ia IIC T4
TR CU 	Available soon!

CERTIFICATION	
PCEC 	Ex ia IIC T4 Gb
INMETRO 	Available soon!
ANZEX 	Ex ia I Ma



WATER AND DUSTPROOF

The 28 II EX carries the most important Ex-certifications and is also tested for drops of up to 3 meters. Additionally it is waterproof and dustproof (IP67). Therefore, the 28 II EX DMM can survive the roughest treatment in the harshest environments.



Multimeter FLUKE 28II EX FOR ZONE 1

FEATURES & FUNCTIONS

- CAT III 1000 V/CAT IV 600 V
- Dustproof, waterproof (IP67)
- Measures up to 1000V / 10A (outside of the Ex-hazardous area)
- Min/Max/Avg and Peak capture
- Low pass filter for accurate measurements on variable speed motor drives
- Input alert
- 4 1/2" digit display (20,000 counts) with backlight

APPROVALS

The Fluke 28II EX combines a large number of worldwide approvals for use in potentially explosive environments – from ATEX to IECEx and NEC – meaning that it is no longer necessary to deploy and integrate different equipment on different continents.

This makes the multimeter a perfect example of portable, intrinsically safe measuring instruments – not least of all due to the numerous features unique to measuring devices in potentially explosive surroundings.



EASY TO USE

- Backlit keypad for extra visibility in poor lit areas
- Large display digits and 2-level backlight
- Long battery life: 400 hours typical (without backlight)

HANDLING BENEFITS

- Only one DMM is needed because of the safe and compact solution which allows safe measurement both inside and outside (max. 10A / 1000V) the Ex-hazardous area
- A separate battery compartment makes it easy to change batteries on fuses










EXTREME RUGGEDNESS

- Completely sealed IP67 rated case
- Water and dustproof
- Meets IEC Overvoltage Electrical Safety Standard EN 61010-1:2001:CAT III 1000V and CAT IV 600V

28 II EX

CAN BE USED WORLDWIDE

ACCESSORIES

ARTICLE NO.	PRODUCT DESCRIPTION	
A0001461	Replacement protection module 440mA f. 28 II EX	
A0009288 	Temperature sensor 80PK-27	
A0005533 	AC Clamp i400 (400A)	
A0001493 	Leather case with strap	
A0009238 	TL175 Twist Guard Test Leads	
A000...	Various Calibration on Request	

TECHNICAL DATA

Ambient temperature	Different temperature ranges for T_{amb} are fixed by the type approved batteries.
Storage temperature	-40°C ... +60°C without batteries
Power supply	3 x AAA, type-proofed
Operating time	approx. 400 h
Dimensions	approx. 210 x 100 x 64 mm (with holster)
Weight	approx. 690 g
Protective rating	IP67

STANDARD DELIVERY

- Fluke 28 II EX
- Ex-holster
- Alligator clips
- Test leads TL175
- Batteries
- Documentation
- CD-ROM

SPECIFICATION

DC voltage	Range: Accuracy:	0.1 mV to 1000 V ± 0.05 % + 1
AC voltage	Range: Accuracy:	0.1 mV to 1000 V ± 0.7 % + 4
DC current	Range: Accuracy:	0.1 µA to 10 A ± 0.2 % + 4
AC current	Range: Accuracy:	0.1 µA to 10 A ± 1.0 % + 2
Resistance	Range: Accuracy:	0.1 Ω to 50 MΩ ± (0.2 % + 1)
Conductance	Range: Accuracy:	60.00 nS ± (1.0 % + 10)
Diode test	Range: Accuracy:	2.0 V ± (2.0 % + 1)
Duty cycle	Range: Accuracy:	0.0 % to 99.9 % Within ± (0.2 % per kHz + 0.1 %) for rise times < 1 µs
Display counts		6000 counts / 19.999 counts in high-resolution mode
Capacitance	Range: Accuracy:	10 nF to 9999 µF ± (1.0 % + 2)
Frequency	Range: Accuracy:	0.5 Hz to 199.99 kHz ± (0.005 % + 1)
Temperature	Range: Accuracy:	-200 °C to +1090 °C [-328 °F to +1994 °F] ± (1.0 % + 10) °C [± (1.0 % + 10) °F]

Error: % of reading + number of digits

REMARKS

Measurement inside the Ex-hazardous area:

$U_i \leq 65V, I_i \leq 5A$

Measurement outside the Ex-hazardous area:

$U_i \leq 1000V, I_i \leq 10A$

EMEA

Germany (Headquarters) ¹

ecom instruments GmbH
Industriestraße 2
97959 Assamstadt
Phone +49 62 94 42 24-0
Fax +49 62 94 42 24-100
sales@ecom-ex.com
¹ also covering Austria

ecom Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com
² also covering Belgium and Luxembourg

France ³

Pepperl+Fuchs EURL
Division Mobile Safety
4 rue Ettore Bugatti
67201 Eckbolsheim (France)
Phone +33.3.88 76 46 84
mobile-safety@fr.pepperl-fuchs.com
³ also covering Algeria, Egypt, Morocco

Italy

ecom instruments srl
Via Gandhi, 15 Galleria
20017 Rho (MI)
Phone +39 02 93 90 92 16
Fax +39 02 93 90 62 97
info.it@ecom-ex.com

Switzerland

Pepperl+Fuchs AG
Sägweg 7
2557 Studen, Bern
Phone +41 32 374 76 76
Fax +41 32 374 76 78
info@ch.pepperl-fuchs.com

Nordics

ecom instruments GmbH
Postbox 304
2970 Hørsholm
Denmark
Phone +45 28 252 575
info.nordics@ecom-ex.com

United Kingdom

ecom instruments ltd
A310, The Wilton Centre,
Redcar, TS10 4RF,
United Kingdom
Phone +44 1642 46 54 00
Fax +44 1642 46 54 02
info.uk@ecom-ex.com

Middle East

Pepperl+Fuchs (ME) FZE
CA - 1 (Near roundabout 8)
PO Box 61398
Jebel Ali Free Zone, Dubai, UAE
Phone +971 4 8838378
Fax +971 4 8838627
pa-info@ae.pepperl-fuchs.com
⁴ also covering Tunisia and Libya

Americas

USA

ecom instruments Inc.
1779 Westborough Drive, Suite 102
Katy, Texas 77449
Phone +1 281 496 59 30
Fax +1 281 496 23 21
sales.us@ecom-ex.com

Asia

South East Asia

Pepperl+Fuchs Pte Ltd
15 Pioneer Turn
P+F GDC Building
Singapore 627577
Tel: +65 6779 9078



Locate your nearest ecom partner on www.ecom-ex.com & www.pepperl-fuchs.com