



# Intrinsically-Safe Magnet Probe Magnet-Ex 12



possible to detect whether or not a solenoid valve is electrically activated.

Connection to electronic circuitry or opening of terminal boxes is rendered unnecessary.

The highly sensitive probe point of the Magnet-Ex 12 only needs to be brought near the coil of a solenoid valve, if the probe shows a red light this indicates that the magnet is activated. In the same manner tests can be carried out on flowmeters or any other equipment that is working magnetically, even when located in hazardous areas.

The Magnet-Ex 12 comes with an integral test magnet that is securely fitted in such a way that it cannot be easily lost. Using this magnet, tests can be carried out to establish the working state of both unit and batteries.



After any check the Magnet-Ex 12 will automatically switch off if it is no longer being used. This ensures a long battery life.

The clip attached to the instrument's side secures it from accidental loss and allows the maintenance engineer to easily carry it at all times.

## Technical data:

Detectable

magnetic fields: alternating, direct and

permanent fields

no contact with test Detection:

object required

Indication: optical, built-in LED

Power supply: 2 x standard batteries

AAA according to IEC LR03 or NiCdrechargeable batteries

Replacing

Storage

only outside the batteries:

hazardous area!

Working -20°C ... +50°C temperature:

-40°C ... +60°C temperature:

Ingress IP 54 protection:

Casing material: metal/plastic probe

point

Dimension: 150 x Ø 18 mm

Weight: 60g (batteries included) For testing solenoid valves, relays, transformers and flow-meters in Ex-hazardous areas.

### Properties:

- highly sensitive
- no contact with test object required
- resistant to dirt

#### Indication:

• optical

## **Built-in test magnet:**

- for testing Magnet-Ex 12
- for battery check

#### Ex-data:

Ex designation: 

**EC-Certificate of Conformity:** PTB 01 ATEX 2018





