

Cable Glands Made of Moulded Plastic with Strain Relief

Series HSK-K-MZ-Ex



www.stahl.de



- > Version Ex e II
- > Degree of protection IP68
- > Usable for portable equipment
- > For flexible connecting cable




13903E00

Zone	ATEX / IECEx					
	0	1	2	20	21	22
For use in		x	x		x	x

E10

WebCode HSKA

Cable Glands Made of Moulded Plastic with Strain Relief Series HSK-K-MZ-Ex



Selection Table

Thread AG	Cable dia. range [mm]	Dimensions [mm]			Order number	Weight kg
		H	SW	GL		
M16 x 1.5	4 ... 8	29	19	15	106073	0.012
M20 x 1.5	6 ... 12	35.5	24	15	106074	0.022
M25 x 1.5	13 ... 18	41	33	11	106075	0.045
M32 x 1.5	18 ... 25	49	42	11	106076	0.065
M40 x 1.5	22 ... 32	58	53	13	106077	0.104
M50 x 1.5	32 ... 38	61.5	60	13	106078	0.174
M63 x 1.5	37 ... 44	62	65/68	14	106079	0.270

Explosion Protection

Global (IECEX)

Gas and dust

IECEX KEM 07.0014X
Ex e II Gb
Ex ta IIIC Da

Europe (ATEX)

Gas and dust

KEMA 99 ATEX 6971 X
⊕ II 2 G Ex e II Gb
⊕ II 1 D Ex ta IIIC Da

Certifications and certificates

Certificates

IECEX, ATEX, Belarus (operating authorisation)

Technical Data

Ambient conditions

Ambient temperature

-20 ... +70 °C

Mechanical data

Degree of protection

IP68 - 10 bar (in specified terminal area)

Material

Cable gland

Polyamide / aluminium

Seal

NBR

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.