










Belastningstabel kl. 10 kædesæt

Anhugnings- måde	1-strengt		2-strengt		3- og 4-strengt		Endeløs 
	Lige 	Sling 	 0-45°	 45-60°	 0-45°	 45-60°	
Kæde dim. mm	WLL i kg						
6	1.400	1.120	2.000	1.400	3.000	2.120	2.240
7	1.900	1.500	2.650	1.900	4.000	2.800	3.000
8	2.500	2.000	3.550	2.500	5.300	3.750	4.000
10	4.000	3.150	5.600	4.000	8.000	6.000	6.300
13	6.700	5.300	9.500	6.700	14.000	10.000	10.600
16	10.000	8.000	14.000	10.000	21.200	15.000	16.000
20	16.000	12.800	22.400	16.000	33.600	24.000	25.600
22	19.000	15.000	26.500	19.000	40.000	28.000	30.000
26	26.500	21.200	37.100	26.500	55.650	39.750	42.400
Lastfaktor	1,0	0,8	1,4	1,0	2,1	1,5	1,6

Sikkerhedsfaktor 4:1

Belastninger gælder for lige/symmetrisk belastede kædeparter iflg. EN 818-6 : 2000

Ulige belastninger:

Ved ulige/asymmetrisk belastede kædeparter skal beregnes 0,5 x WLL!

