

ZONE 1/21



## < IS520.1 >

The IS520.1 is an industrial smartphone with current technology. It combines modern design, updated technology and robustness of an industrial product.

## TECHNICAL FEATURES



ATEX approval:  
EX-zone 1/21  
Ⓜ II 2G Ex ib IIC T4 Gb  
Ⓜ II 2D Ex ib IIC T135°C Db IP6X



IECEx approval:  
EX-zone 1/21  
Ex ib IIC T4 Gb  
Ex ib IIC T135°C Db IP6X



Approved for North America:  
Class I, II, III Division 1  
Groups A B C D E F G, T4  
Intrinsically Safe



Approved for Russia:  
1Ex ib IIC T4 Gb X  
Ex ib IIC T135°C Db X  
IP64



Android™ 7.1



GSM: 850/900/1800/  
1900MHz  
WCDMA:  
900/1800/2100 or  
850/1900/2100MHz  
LTE-FDD: B1/B3/B7/B20/B28  
LTE-TDD: B38/B39/B40/B41  
TD: B34/B39



5GHz: IEEE 802.11  
b/g/n/r/AC with hotspot



Bluetooth® 4.1 LE



size: 155 x 80 x 25 mm,  
weight: 325 g



external memory  
microSD up to 32 GB



Qualcomm Snapdragon  
625 (MSM8953)  
3 GB RAM  
32 GB internal memory  
22 GB accessible



2 cameras: 8 MP rear  
camera and 5 MP front  
camera



Dual micro SIM



Near Field  
Communication



SOS-key



magnetic charging port

## FURTHER FEATURES



waterproof: 1 hour  
up to 2 m, impervious to  
dust and microparticles



operation range from  
-20 °C to 60 °C



drop-protection,  
tested against: extreme  
temperatures, barometric  
pressure, humidity and  
vibrations.



4,5" RugDisplay-Glas  
multi capacitive touch-  
screen with a resolution  
of 854 x 480 pixel



usable with gloves



amplified loudspeaker



3600 mAh battery



GPS, AGPS, Glonass,  
BeiDou



Location, gyroscope,  
gravity, ambient light,  
magnetic- and proximity



Push-To-Talk  
PTT ready (third party  
application provided)



Loneworker protection  
LWP ready (third party  
application provided)



quick charge

## CONTENTS

Smartphone, battery, i.safe PROTECTOR 2.0 USB cable, i.safe PROTECTOR 3.0 USB cable, charger, quick start manual and safety instructions