




803 

GOLFARE MASCHIO 8.8
EYE BOLT 8.8
ANNEAU DE LEVAGE MALE 8.8
RINGSCHRAUBEN 8.8



WORKING LOAD LIMIT W.L.L. (t)



Codice Code Code Code	Misura Size Mesure Abmessung	WORKING LOAD LIMIT W.L.L. (t)						Coppia max di serraggio Max tightening couple Max couple de serrage Max Drehmoment (Nm)
		0° 1 braccio Single leg 1 brin 1 Strang	0° 2 bracci 2 legs 2 brins 2 Stränge	0°-45° 2 bracci 2 legs 2 brins 2 Stränge	45°-60° 2 bracci 2 legs 2 brins 2 Stränge	0°-45° 3/4 bracci 3/4 legs 3/4 brins 3/4 Stränge	45°-60° 3/4 bracci 3/4 legs 3/4 brins 3/4 Stränge	
C80306	M6x13	0,4	0,8	0,14	0,1	0,2	0,14	3,5
C80308	M8x13	0,8	1,6	0,28	0,2	0,4	0,28	8
C80310	M10x17	1	2	0,35	0,25	0,5	0,35	16
C80312	M12x21	1,6	3,2	0,56	0,4	0,8	0,56	28
C80314	M14x21	3	6	1	0,75	1,5	1	45
C80316	M16x27	4	8	1,4	1	2	1,4	70
C80318	M18x27	5	10	1,8	1,25	2,5	1,8	95
C80320	M20x30	6	12	2,1	1,5	3	2,1	135
C80322	M22x36	7	14	2,4	1,75	3,5	2,4	182
C80324	M24x36	8	16	2,8	2	4	2,8	230
C80327	M27x45	10	20	3,5	2,5	5	3,5	343
C80330	M30x45	12	24	4,2	3	6	4,2	465
C80333	M33x54	14	28	4,8	3,4	6,8	4,8	632
C80336	M36x54	16	32	5,6	3,9	7,8	5,4	814
C80342	M42x63	24	48	8,4	5,9	11,8	8,2	1304
C80348	M48x68	32	64	11,2	7,8	15,6	10,9	1981
C80356	M56x78	36	72	12,6	8,8	17,6	12,3	3000
C80364	M64x90	45	90	15,7	11	22	15,4	4736

Coefficiente di sicurezza: 4
 Safety ratio: 4
 Coefficient de sécurité: 4
 Sicherheitsfaktor: 4

Avvitare a mano
 To be screwed by hand
 A visser a main
 Von Hand aufschrauben