

Lite-Ex[®] PL

10e HIGH PERFORMANCE LED

AN ULTRA LIGHT AND BRIGHT TORCH, DESIGNED FOR EVERYDAY USE IN HAZARDOUS AREAS.

Despite its compact dimensions, the Lite-Ex[®] PL 10e is equipped with all of the features of its larger sibling.

It comes with the tried and tested, wear-resistant ring switch and a high performance LED. Its sophisticated lens ensures even and consistent illumination.



Lite-Ex[®] PL 10e LED FLASHLIGHT FOR ZONE 0 / 20

TECHNICAL DATA	
Ambient temperature	-20 °C ... +50 °C
Storage temperature	-30 °C ... +60 °C (without batteries)
Power supply	3 x LR03 / AAA (type-tested)
Light source	High performance LED
Luminosity	3,000 lux (at a distance of 1 m)
Luminous flux	64 lumens
Operating time	approx. 55 hrs
Dimensions	147 x 36 x 36 mm
Weight	approx. 120 g (with batteries)
IP protection class	IP65 / IP67
ESD protection	Anti-static housing
CE-designation	CE 0102















SCOPE OF DELIVERY

- Lite-Ex[®] PL 10e
- Batteries
- Belt clip
- Wrist strap
- Documentation

FEATURES

- Zone 0/20
- High performance LED
- Luminosity: 3,000 lux (at a distance of 1 m)
- Extremely light and compact. Weight: only 120 g including batteries
- Operating time: approx. 55 hours
- Ring switch, easy to use
- Scratch-resistant thanks to the coated protective disc
- Rugged polyamide housing
- Diaphragm valve for pressure compensation
- Removable belt clip

ACCESSORIES

	ARTICLE NO.	PRODUCT DESCRIPTION
		Belt clip
		Hand strap
		Ring switch
		Sealing kit
		Replacement lens
		Lamp head (only plastic part)
		Leather holster

EX DATA



Ⓜ II 1 G Ex ia op is IIC T4 Ga IP65
Ⓜ II 1 D Ex ia IIIC T130°C Da IP65



Ex ia op is IIC T4 Ga IP65
Ex ia IIIC T130°C Da IP65