

# Lite-Ex<sup>®</sup> PL 30e

UPDATE OF  
THE BESTSELLER

## SURPASSES ALL LED FLASHLIGHTS ON THE MARKET.

The Lite-Ex<sup>®</sup> PL 30e flashlight from ecom surpasses all other LED flashlights on the market.

The integrated 3 Watt LED, which is powered by 3 LR14 batteries, allows work to be conducted with extremely bright light for hours at a time.

In the new generation, a special reflector enables the illumination of larger surfaces.

The ergonomically designed, anti-static plastic housing ensures the flashlight fits perfectly in your hand and also provides excellent anti-slip protection.

The high IP65 protection rating prevents the permeation of dust and jet water. Use in harsh conditions is therefore not a problem.









## SIMPLE AND RELIABLE TWIST MECHANISM

The switch-on mechanism is yet another outstanding feature - the flashlight is switched on via a sturdy rotating ring. This eliminates annoying malfunctions and repairs due to a faulty switch, thereby saving the user both time and money.

## FEATURES

- Zone 0 / 20
- 1x high performance LED (3 Watt)
- 204 Lumen
- Ring switch
- Rugged housing
- High IP protection class IP65
- Diaphragm valve for pressure compensation

## ACCESSORIES

		PRODUCT DESCRIPTION
		Leather holster
		Sealing kit
		Replacement lens
		Ring switch

## Lite-Ex<sup>®</sup> PL 30e



LED FLASHLIGHT FOR ZONE 0 / 20



## SCOPE OF DELIVERY

- Lite-Ex<sup>®</sup> PL 30e
- Batteries
- Wrist strap
- Documentation

## EX DATA

	⊕ II 1 G Ex ia op is IIC T4 Ga IP65 ⊕ II 1 D Ex ia IIIC T130 °C Da IP65
	Ex ia op is IIC T4 Ga IP65 Ex ia IIIC T130°C Da IP65

## TECHNICAL DATA

<b>Ambient temperature</b>	-20 °C ... +50 °C
<b>Storage temperature</b>	-30 °C ... + 60 °C (without batteries)
<b>Power supply</b>	3x LR 14 (type-tested)
<b>Light source</b>	1x 3 Watt LED
<b>Luminosity</b>	5,000 lux (at a distance of 1 m)
<b>Luminous flux</b>	204 lumens
<b>Operating time</b>	> 48 hrs (continuous operation)
<b>Dimensions</b>	approx. 220 x 55 / 42 mm (L x Ø)
<b>Weight</b>	approx. 530 g
<b>IP protection class</b>	IP65
<b>ESD protection</b>	Anti-static housing
<b>CE-designation</b>	CE 0102