


VESX50-IP

2 Pole Magnetic Grounding Clamp

Ex h

Global certification available

Online Enquiry >



VESX50-IP



Grounding clamps are typically designed around torsion or compression springs. The spring type grounding clamps are ideal for many different applications. However, attaching a spring based grounding clamp to a flat or curving surface is not normally possible e.g. the body of a drum.

Newson Gale have designed a 2 pole grounding clamp that capitalises on the power of magnetism and tungsten carbide tips to provide a strong low resistance connection (≤ 10 Ohms) to any ferrous metal surface e.g. body of a drum, tote, IBC, etc. This will allow drums to be filled, the cover fitted complete with extract connection over the open top and still ground the ferrous metal based drum with the VESX50-IP 2 pole magnetic grounding clamp.

The VESX50-IP 2 pole magnetic grounding clamp is fully compatible with the Newson Gale Bond-Rite and Earth-Rite monitoring systems that provide the customer with visual indication and interlock capability. Using this clamp and these systems will help the user to comply with International Standards, Guidance and Recommended Practices IEC TS 60079-32-1, NFPA77 and API RP 2003 in achieving a metal on metal to ground connection of ≤ 10 Ohms before the process starts and therefore mitigate static build up.

The body and integral handle of the VESX50-IP 2 pole magnetic grounding clamp are made from stainless steel (A2/SS304) for long life and corrosion resistance. Two sharp spring loaded tungsten carbide tips are used to penetrate coatings and make a low resistance connection (≤ 10 Ohms) to ground possible.

Due to the strength of the two Neodymium magnets the clamp is supplied with a sacrificial metal keeper that will need to be removed before the clamp is used. The sacrificial keeper will help focus away the magnetic field from other ferrous objects until the clamp is installed.

An optional stowage point is available for the VESX50-IP 2 pole magnetic grounding clamp. It allows the clamp to have a designated stowage point close to the item of ferrous metal based plant that the operator can use to park the clamp safely when it is not in use.

2 Pole Magnetic Grounding Clamp Key Benefits

- > **Positive Contact** – the powerful combination of sharp spring loaded tungsten carbide tips complimented by the strength of the two Neodymium magnets ensure that coatings, product deposits or corrosion does not prevent the clamp from making a low resistance connection (≤ 10 Ohms) to the equipment to be grounded.
- > **Ergonomic** – 2 Pole magnetic clamps have an integral handle and are therefore easy to grip, roll on and roll off when the operators have to make repetitive daily grounding connections.
- > **Long Term Value** – additional value is provided by the corrosion resistant and mechanically robust stainless steel construction which helps reduce long term replacement costs that are typical of lower quality grounding clamps.

VESX50-IP

2 Pole Magnetic Grounding Clamp


VESX50-IP

What are the benefits of using tungsten carbide teeth?

Tungsten carbide is one of the hardest materials used in industry today. When used in combination with very strong Neodymium magnets, has the capability to continuously bite through coatings, rust or product deposits that a basic alligator clip or welding clamp would struggle to achieve. Sharp tungsten carbide teeth are a standard feature of Newson Gale's heavy duty clamps.

Magnetic Static Grounding Clamp

Applications	Grounding & bonding ferrous metal objects ranging from 55 gallon drums to large metal totes & IBCs
Clamp Material	Stainless Steel 304 Body Stainless Steel Springs Nylon Viton O-Ring Tungsten Carbide Tips Neodymium Magnets
Operating Temperature	-40°C to +60°C
Dimensions	133 mm x 36 mm x 96 mm (cable and connector add another 325mm to the length)
Weight	0.52 kgs (nett)
IECEX Certification	Ex h IIC T6 Ga Ex h IIIC T85°C Da, Ta = -40°C to +60°C IECEX EXV 20.0033
Wire Diameter	2 x 1.00 mm ² copper (Overall OD 7.5 mm / 0.3")
Cable to be used with clamp	3 m (10 ft), 5 m (16 ft), 10 m (32 ft) or 15 m (50 ft) 2 pole Cen-Stat blue spiral cable with anti-UV / static dissipative Hytrex coating



Tungsten carbide teeth are designed to penetrate rust, coatings and product deposits to achieve a low resistance connection

Clamp Options



Magnetic Clamp Storage Point

Copyright Notice

The website and its content is copyright of Newson Gale Ltd © 2020. All rights reserved.

Any redistribution or reproduction of part or all of the contents in any form is prohibited other than the following:

- you may print or download to a local hard disk extracts for your personal and noncommercial use only
- you may copy the content to individual third parties for their personal use, but only if you acknowledge the website as the source of the material

You may not, except with our express written permission, distribute or commercially exploit the content. Nor may you transmit it or store it in any other website or other form of electronic retrieval system.

Right to change

This document provides general information only and may be subject to change at any time without notice. All information, representations, links or other messages may be changed by Newson Gale at any time without prior notice or explanation.

Newson Gale is not obliged to remove any outdated information from its content or to expressly mark it as being outdated. Please seek the advice of professionals as necessary regarding the evaluation of any content.

Disclaimer of liability

The information provided in this Datasheet is provided by Newson Gale without any representations or warranties, expressed or implied, as to its accuracy or completeness. The liability of Newson Gale for any expenses, losses or actions incurred whatsoever by the recipient as a result of the use of this Datasheet shall be excluded.

Leading the way in hazardous area static control



www.newson-gale.co.uk

2/2

United Kingdom
Newson Gale Ltd
Omega House
Private Road 8
Colwick, Nottingham
NG4 2JX, UK
+44 (0)115 940 7500
groundit@newson-gale.co.uk

United States
IEP Technologies LLC
417-1 South Street
Marlborough, MA 01752
USA
+1 732 961 7610
groundit@newson-gale.com

Deutschland
IEP Technologies GmbH
Kaiserswerther Str. 85C
40878 Ratingen
Germany
+49 (0)2102 58890
erdung@newson-gale.de